



Description

Features

- General purpose SMD LED luminaires.
- Special designed opal diffuser (PMMA) with framing.
- Shadeless and homogenous light output by using impermeable micron LED technology.
- Problem free stock management with three separate power option in same luminaire.
- SMD LED
- IP40 protection class.
- Choice of patterns and colour temperatures on request.
- Available in seven different colour temperatures 6500K (cool white), 6000K (cool white), 5700K (cool white), 5000K (cool white), 4000K (natural white), 3000K (warm white), 2700K (warm white).
- Opal diffuser options for architectural and aesthetic designs.
- Fully complies with RoHS requirements.
- Recyclable ♻️ raw materials.

Materials

- Canopy; electrostatic powder painted high quality sheet steel housing
- Diffuser; acrylic (PMMA)

Applications


- Offices
- Shops
- Hotels
- Restaurants
- Meeting rooms
- Cafeterias
- Shopping malls
- Education fields
- Healthcare fields
- Kitchens
- Terminals
- Schools

Technical Data

- 220-240V AC 50/60 Hz ECG
- Dimensions: 595x595x90mm

Standards

- CE, RoHS, EN60598-2-2





Standard



Protection Gloves



E1/E3 Emergency Kit



Recessed Luminaires							
LED Concept Tablet CL9014 Opal Diffuser							
IP40 / RAL 9006							
	W (mm)	L (mm)	h (mm)	Item /Box	Weight (kg)	Order Code	
25W	595	595	90	4	4.30	L9014-LED025-ECG	
28W/32W/36W	595	595	90	4	4.30	L9014-LED03P-ECG	
Option Code							
-T1. T15,T25 Lay-In Ceiling (Standard)	-CW. Colour Temperature 6500K		-NW. Colour Temperature 4000K (Standard)		-EL1.Emergency Battery 1 Hour		
-T2. Recessed Ceiling Installation Tools	-CW. Colour Temperature 6000K		-WW. Colour Temperature 3000K		-EL3.Emergency Battery 3 Hours		
-T3. Clip-In Ceiling	-CW. Colour Temperature 5700K		-WW. Colour Temperature 2700K				
	-CW. Colour Temperature 5000K						
According to your preference, please add the Option Code at the end of the Order Code							

Recessed Luminaires